



## PRODUCT INFORMATION

<b>Product</b>	<b>Masking Tape (High Temperature ) MKT- 05 / MKT - 05Y</b>	
<b>Brand</b>	Loytape	
<b>Product Description</b>	MKT- 05 and MKT- 05Y High Temperature Masking Tapes are specially suited for high temperature spray painting applications. Suitable for all vehicles where high temperature holding is required.	
<b>Construction</b>	Backing	- Crepe paper treated with heat resistant saturant
	Adhesive	- Rubber based pressure sensitive cured adhesive system
	Colour	- Buff (MKT - 05 grade) / Yellow (MKT - 05Y grade)
<b>Sizes</b>	Standard widths	6 mm, 9 mm, 12 mm, 18 mm, 24 mm, 36 mm, 48 mm
	Standard lengths	20 yards
	Core size (ID)	3 inch (Equivalent to 76 mm)
	Special sizes	Customised width and length available on request subject to minimum order quantity. Jumbo roll in width of 1500 mm available.
<b>Packing</b>	<b>Width x length</b>	<b>Rolls/Carton</b>
	6 mm x 20 yards	576
	9 mm x 20 yards	384
	12 mm x 20 yards	288
	18 mm x 20 yards	192
	24 mm x 20 yards	144
	36 mm x 20 yards	96
	48 mm x 20 yards	72
<b>Physical Properties</b>	Peel adhesion to steel	850 g/25 mm
	Total thickness	0.155 mm
	Heat resistance	Up to 150°C for 1 hour
	The technical information exhibited above represent average values obtained in our laboratory testing only and should not be used for specifications purposes.	
<b>Features</b>	<p>Good crepe backing with natural rubber cured adhesive for excellent holding strength to prevent lifting.</p> <p>Soft crepe backing allows masking to wrap around target object.</p> <p>Sticks to a wide variety of surfaces.</p> <p>Good paint resistance (Resists seep through).</p> <p>No tacky residue left on surface when removed.</p> <p>Suitable for use as bandleering tape</p>	
<b>Storage Condition</b>	To be stored at room temperature. Keep away from prolonged exposure to direct sunlight.	
<b>Important Notice</b>	<p>Loytape Industries Sdn Bhd does not accept any responsibility directly or indirectly for any consequential loss or damage as a result of our recommendations. You are hereby advised to conduct your own tests to determine the suitability of the products for your applications.</p> <p>Manufactured under Loytape ® strict quality system registered under ISO 9001</p>	

For Sales within Malaysia, Kindly Contact any of the Branches Nearest to You | (Business Hours : 8.30am - 5.30pm, Mon - Fri)

Branches	Address	Tel No	Fax No	E-mail
Penang	1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang.	604-3907049	604-3997561	sales-pg@loytape-marketing.com.my
Kuala Lumpur	31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.	603-92008199	603-92007990 / 8990	sales-kl@loytape-marketing.com.my
Johor Bahru	11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor.	607-3559968	607-3559967	sales-jb@loytape-marketing.com.my
Ipoh	10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak.	605-5365916	605-5362717	sales-ipoh@loytape-marketing.com.my
Corporate Office				

Loytape Industries Sdn Bhd : 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang, Malaysia.

604-3907049

604-3993030

[stick2us@loytape.com.my](mailto:stick2us@loytape.com.my)