



## LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,  
Kawasan Perusahaan Perai,  
13600 Perai, Seberang Perai, Penang, Malaysia  
Tel No. 604-3907049, Fax No. 604-3993030.  
E-mail : stick2us@loytape.com.my  
Website: www.loytape.com.my

### TECHNICAL INFORMATION

**PRODUCT NAME : BROWN MASKING TAPE GENERAL PURPOSE**

**PRODUCT CODE : MKT-15**

#### FEATURES

- The crepe paper masking tape exhibits high adhesion, high cohesion and high holding power.
- Specially formulated adhesive allows no tacky residue on surface when removed.

#### TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	<b>Min 600</b>
2.	Tack Rolling Ball	ball no.	<b>Min 5</b>
3.	Adhesive Coating Weight	g/m <sup>2</sup>	<b>34 ± 5</b>
4.	Total Thickness	mm	<b>0.135</b>
5.	Holding Power	mins	<b>Min 1440</b>
6.	Solvent Resistance	-	<b>Average</b>
7.	Heat Resistance	1 hr, °C	<b>80</b>

#### PROPERTIES OF RAW MATERIAL

No.	Particular	
1.	Carrier	<b>Crepe Paper</b>
2.	Basic Weight	<b>60 gsm</b>
3.	Colour	<b>Brown</b>

#### APPLICATION AND USAGE

- For various masking, holding, bundling, sealing light to medium paper carton packaging and colour identification.
- For industrial, home and office use.
- Heat resistance at 80 °C for 1 hour.

#### LAB TEST CONDITIONS

Temperature : 20 ± 5 °C

Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

**SHELF LIFE: 12 MONTHS**

**Mar 2020**

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.

